



Vaso autoclave orizzontale con membrana intercambiabile per circuiti di acqua sanitaria.
 Horizontal pressure tank with replaceable membrane for pressurized systems of sanitary water.
 Réservoir sous pression horizontal à vessie remplaçable pour systèmes d'eau sanitaire.
 Horizontales Druckausdehnungsgefäß mit austauschbarer Membrane für Trinkwassersysteme.

Temperatura d'esercizio
 Working temperature
 Température d'exercice
 Betriebstemperatur

- 10° C
 + 100° C

Colore della verniciatura esterna
 External finish color
 Couleur de la peinture externe
 Externe Beendenfarbe

RAL 5015

Membrana in gomma
 Rubber membrane
 Vessie en gomme
 Gummimembrane

EPDM

Controflangia zincata - Counter flange galvanized
 Contre-bride galvanisée - Gegenflansch Verzinkt



Garanzia sul prodotto mesi: - Warranty months:
 Garantie mois: - Monate Garantie:

24

Modello Model Modèle Model	Codice Code Code Code	Altezza Height Hauteur Höhe	Diametro Diameter Diamètre Durchmesser	Lunghezza Length Longeur Länge	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck	Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck	Imballo Packing Emballage Verpackung	Attacco Connection Raccordement Anschluss
		H (mm)	Ø (mm)	L (mm)	(bar)	(bar)	(mm)	(inch)
VA018	AAGOE11B01CC1	305	280	430	10	1,5	(Pz4) 520X580X610	1"
VA024	AAIOE11B01EC1	300	280	483	10	1,5	(Pz4) 520X580X610	1"
VA035	AAJOE11B01EA1	376	365	440	10	1,5	(Pz1) 380X400X460	1"
VA050	AAKOE11B01EA1	380	365	585	10	1,5	(Pz1) 380X400X590	1"
VA060	AALOE11B01EA1	385	365	665	10	1,5	(Pz1) 380X400X700	1"
VA080	AAMOE11B01EA1	430	410	725	10	1,5	(Pz1) 430X450X735	1"
VA0100	AANOE11B11EA1	520	495	685	10	1,5	(Pz1) 510X540X700	1"
VA0150	AAPOE11B11EA1	585	550	820	10	1,5	(Pz1) 570X610X850	1"

Temperatura d'esercizio
 Working temperature
 Température d'exercice
 Betriebstemperatur

- 10° C
 + 100° C

Colore della verniciatura esterna
 External finish color
 Couleur de la peinture externe
 Externe Beendenfarbe

RAL 5015

Membrana in gomma
 Rubber membrane
 Vessie en gomme
 Gummimembrane

EPDM

Controflangia verniciata - Painted counter flange
 Contre-bride peinte - Lackierter Gegenflansch



Garanzia sul prodotto mesi: - Warranty months:
 Garantie mois: - Monate Garantie:

24

Modello Model Modèle Model	Codice Code Code Code	Altezza Height Hauteur Höhe	Diametro Diameter Diamètre Durchmesser	Lunghezza Length Longeur Länge	Pressione massima d'esercizio Maximun working pressure Pression maximale d'exercice Maximaler Betriebsdruck	Pressione di precarica standard Standard precharge pressure Pression de précharge standard Vordruck	Imballo Packing Emballage Verpackung	Attacco Connection Raccordement Anschluss
		H (mm)	Ø (mm)	L (mm)	(bar)	(bar)	(mm)	(inch)
VA0200	AAQOG21B11FA1	628	600	920	10	2	(Pz1) 620X630X1030	1 1/4"
VA0300	AASOG21B11FA1	680	650	1082	10	2	(Pz1) 680X700X1290	1 1/4"

Controflangia inox AISI 304 disponibile su richiesta. - Stainless steel AISI 304 counter flange available on request.
Contre bride inox AISI 304 disponible sur requête. - Inox Flansch AISI 304 auf Anfrage.

Marchi CE secondo la Direttiva - CE marked according to Directive - Avec le marque CE selon la Directive - CE Kennzeichnung
 2014/68/UE